

Calix jet/ Cáliz

This fountain nozzle produces a more turbulent **sheet of water** than the mushroom jet and rises to a greater height. The film of water leaves the fountain nozzle at an exit angle to produce a parabolic pattern, and when it falls, the film is broken to **create a calix shape**. It generates more noise in normal operation than the mushroom jet because the film of water is broken, making it **suitable for outdoor fountains** as a feature combined with other higher jets.

Esta boquilla genera una **lámina de agua** con un régimen algo más turbulento que el hongo y que levanta más altura. Dicha lámina sale de la tobera con un ángulo de salida lo que provoca un tiro parabólico y es en su caída cuando la lámina se rompe **generando una forma de cáliz**. Genera más ruido en su funcionamiento normal que el hongo, lo que la hace **adecuada para fuentes de exterior**, como efecto combinado con otros principales.



Nozzles/
Boquillas

Brass + Stainless steel

Latón + Acero Inox.

ON STOCK

304



Water appearance/ Aspecto del agua

Wind resistance/ Resistencia al viento

Splash/ Salpicadura

Sound level/ Nivel de sonido

Visibility/ Visibilidad


Clear/ Cristalino

☆☆

☆☆

☆☆

☆☆☆☆



Dimensions/ Dimensiones						Performance/ Rendimiento													
Reference/ Referencia	Connection/ Conexión A	Length/ Long. B (mm)	Angle/ Ángulo (α)	Jets thickness/ Espe- sor lámina (mm)	Weight/ Peso (kg)	Diameter/ Diametro (cm) D	40	60	80	100	120	140	160	180	200	250	300		
F2633409	G 3/4" F/H BSP-NPT	135	70°	2,0	0,30	l/min	27,0	30,5	33,5	36,0	38,0	40,0	42,0						
						m.c.a	0,74	0,84	0,92	1,00	1,06	1,12	1,18						
						Height (cm) H	27,0	31,5	36,0	40,0	44,5	48,5	53,0						
F2631003	G 1" F/H BSP-NPT	170	70°	5,0	0,60	l/min	35,0	43,0	50,0	54,5	59,0	62,0	65,5	68,0					
						m.c.a	0,90	1,10	1,30	1,55	1,75	1,95	2,18	2,40					
						Height (cm) H	31,0	37,0	41,0	45,0	48,0	51,0	53,0	55,0					
F2632004	G 2" F/H BSP	210	70°	7,0	1,00	l/min	64	75	85	95	104	114	120	125	129				
						m.c.a	0,35	0,90	0,43	0,47	0,49	0,52	0,54	0,56	0,59				
						Height (cm) H	28,0	31,0	34,0	37,0	40,0	43,0	46,0	49,0	52,0				
F2643006	G 3" F/H BSP	313	80°	5,5	4,00	l/min			110	126	134	150	158	166	174	190	206		
						m.c.a			0,50	0,55	0,56	0,60	0,65	0,72	0,80	0,95	1,10		
						Height (cm) H			37,0	42,0	45,0	50,0	53,0	57,0	60,0	80,0	100,0		

Further information at www.saferain.com | Más información en www.saferain.com