

# Gushing Nozzle



OASE's Gushing nozzle is aptly named. Creating a long, sheeting throw in a compact fan shape, the Gushing nozzle features a stream thickness of 1/4" and a projection angle of 30 degrees and an elevation angle of 45 degrees. Used alone, this nozzle is particularly suited to installations

requiring an inward spray from pond corners, but an especially striking effect is achieved when grouped with others in the center of a pond or pool spraying outward around a vertical stream centerpiece.



## Technical description:

- The Gushing nozzle is water level independent and can be located in "dry" areas.
- Construction is of cast brass.
- Gushing nozzles should not be mounted in swimming pools where they may cause injury. Use with swimming pools requires the jet to be mounted in a flush niche to protect the swimmers.
- The Gushing nozzle has female BSPP threads.

Visibility					
Noise Level					
Splash					
Wind Stability					
Energy Efficiency					

# Gushing Nozzle

Display Throw	115-15 T								Display Throw
Feet	GPM	TDH	Height	Width	LPM	BAR	Height	Width	Meters
1'-8"	24.79	1.27	3.9"	10"	94.2	0.04	10cm	25cm	0.50
2'-6"	29.71	1.90	5.9"	13"	112.9	0.06	15cm	33cm	0.75
3'-3"	34.68	2.53	7.9"	17"	131.8	0.08	20cm	42cm	1.00
4'-1"	39.47	3.17	10.2"	20"	150.0	0.10	26cm	50cm	1.25
4'-11"	44.37	3.84	13.0"	23"	168.6	0.12	33cm	58cm	1.50
5'-9"	49.29	4.50	15.7"	26"	187.3	0.14	40cm	67cm	1.75
6'-7"	66.03	5.07	18.9"	30"	250.9	0.15	48cm	75cm	2.00
8'-2"	64.00	6.37	24.4"	36"	243.2	0.19	62cm	92cm	2.50
9'-10"	73.79	7.64	30.3"	43"	280.4	0.23	77cm	108cm	3.00
11'-6"	83.55	8.94	36.2"	49"	317.5	0.27	92cm	125cm	3.50
13'-1"	93.37	10.21	41.7"	56"	354.8	0.31	106cm	142cm	4.00
14'-9"	103.18	11.47	47.6"	62"	392.1	0.34	121cm	158cm	4.50
Mat'l	Brass								Mat'l
Weight	2.50Kg				5.50lbs				Weight
Article #	697-551								Article #
ID #	50976								ID #
Part #	89041								Part #

Gushing Nozzle 115-15 T  
89041

